




Spill Structure


large variations in instantaneous beam intensity → high hit occupancy





beam-line Cherenkov monitor for beam diagnostics:






- → beam diagnostics: measurement of RF-bucket by RF-bucket intensity
- → trigger inhibit: veto on single RF buckets as a function of intensity,
 ½ beam inhibited due to 10x expected beam/RF-bucket

Duty Factor Measurements

- studying the uniformity of the beam




- confirmed that longitudinal quad damper improves
 DF
- increased RF voltage in MI during flattop
- test of feedback system installed to reduce 360Hz component in beam, might also reduce low frequency variations; RF voltage

based on real dimuon events, affected by coincidence window and saturation

Spectrometer Status and Plans

Operational



Target

FMAG (2000A) KMAG (1600A)

Hodoscopes

Drift Chambers

DAQ

liquid targets: H₂ and D₂, solid state targets: C, Fe, W; positions calibrated, ongoing issue of target position alerts (work in progress)

operational, improved cooling, ongoing effort of bleeding air, precise magnetic field calibration (<1%))


timed in precisely (+/- 1ns), high efficiency, ongoing HV tuning (sagging?), well tested during trigger studies

operating stable (also at 2e12 ppp), high efficiency, electronics working well after the failure due to the power outage (see previous AEM presentation)

continuous data taking, reduced DAQ dead time < 140us

Data Taking

SeaQuest Integrated Protons 6/8/14 - 6/15/14



inhibiting 30% of beam

Status of the Analysis

data taking:



- presentation of first preliminary physics results at DNP 2014
- track and dimuon reconstruction (from small data sample):

